



[Enlarge](#)



Registered Design No.: 9911180, 1M002

[Download Manual](#)

### SPECIFICATIONS

| Basic Functions                            | Range                      | Best Accuracy |
|--|----------------------------|---------------|
| DC Voltage                                 | 200mV/2000mV/20V/200V/500V | ±(0.5%+2)     |
| AC Voltage                                 | 200V/500V                  | ±(1.2%+10)    |
| DC Current                                 | 2000µA/20mA/200mA/10A      | ±(1%+2)       |
| Resistance                                 | 200Ω/2000Ω/20kΩ/200kΩ/20MΩ | ±(0.8%+2)     |
| Temperature (°C)                           | -40°C ~ 1000°C             | ±(1%+3)       |
| Special Functions                          |                            |               |
| Diode                                      | ✓                          |               |
| Continuity Buzzer                          | ✓                          |               |
| Transistor                                 | ✓                          |               |
| Data Hold                                  | ✓                          |               |
| Display Backlight*                         | ✓                          |               |
| Low Battery Display                        | ✓                          |               |
| Input Impedance for DC Voltage Measurement | ✓                          |               |
| Max Display                                | 1999                       |               |

### GENERAL CHARACTERISTICS

|                              |  |
|------------------------------|--|
| Power                        | 9V Battery (6F22)  |
| LCD Size                     | 48 x 16mm  |
| Product Colour               | Body - Grey, Holster - Red   |
| Product Net Weight           | 160g   |
| Product Size                 | 130 x 74 x 41mm  |
| Standard Accessories         | Test Lead, Battery, English Manual, Holster  |
| Optional Accessories*        | Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2) |
| Standard Packing             | Gift Box   |
| Standard Quantity Per Carton | 60 pcs   |
| Standard Carton Measurement  | 536 x 310 x 305mm (0.051 CBM per standard carton)  |
| Standard Carton Gross Weight | Around 16.7kg  |

\*Available at Extra Cost  
 Specifications and other information are subject to change without further notice.

[Back to main menu](#)