



### Overview

Lead time	Usually in Stock
-----------	------------------

### Physical

Cable length	1.00 m
Depth	18 cm
Height	11.9 cm
Net weight	1.96 kg
Width	9.5 cm

### Input

Network frequency	50 Hz
Plug standard	Schuko CEE 7/7P
Input voltage limits	184...284 V
Input voltage	230 V

### Output

Rated power in W	750 W
Maximum configurable power in W	750 W
Output voltage	230 V

### Conformance

Product certifications	EAC
------------------------	-----

### Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...90 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-20...50 °C
Storage altitude	0.00...1015.90 m

### Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Liquid value	0

### Surge Protection and Filtering

Surge energy rate	148 J
-------------------	-------

### Packing Units

Package 1 Weight	1.96 kg
Package 1 Height	22.8 cm
Package 1 width	9.8 cm
Package 1 Length	12.5 cm
SCC14	10731304341830
Number of Units in Package 2	12
Package 2 Weight	25.50 kg
Package 2 Height	7112.00 mm
Package 2 width	8128.00 mm
Package 2 Length	12141.20 mm

### Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

### Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------